














# URALSHINA (Ural Tyre Plant)








## TRUCK & LIGHT TRUCK TYRES

Size	Model type	Effective Load N	Pressure at effective load, MPa	Max Speed km/h	Outer diam. mm	Section Width mm	Static Radius mm	Weight tyre/tube kg	Tread Pattern
-1-	-2-	-3-	-4-	-5-	-6-	-7-	-8-	-9-	-10-
8,25-20	IK-6AM-P	16190	0,48	100	970	234	462	35.7/3.5	
9,00-20	VI-244UD-1	21970	0,63	100	1028	270	488	47.5/4.5	
9,00R20	IN-142BM	21,97kgf.max	660 kPa (single) 20,21 kgf.max (double)	100	1018	258	475	55	
12,00-18	K-70	18142	0,34	80	1084	337	505	55.0/7.7	
12,00-20	M-93	21575	0,41	80	1142	335	530	63.0/8.2	

-1-	-2-	-3-	-4-	-5-	-6-	-7-	-8-	-9-	-10-
8,40-15	YA-192	7600	0,26	110	791	218	377	20.8/1.1	
8,40-15	YA-245	7600	0,26	110	777	218	364	18.9/2.1	







Passenger Tyres

165/70R13	C-129	3875	0,20	160	580	177	265	7.6/1.1	
175/70R13	C-129	3875	0,20	160	580	177	265	7.6/1.1	
165/70R13	C-135	3972	0,20	190	580	176	265	7.6/1.1	
175/70R13	C-135	3972	0,20	190	580	176	265	7.6/1.1	



-1-	-2-	-3-	-4-	-5-	-6-	-7-	-8-	-9-	-10-
165/70R13	C-140	3875	0,20	160	580	176	265	7.6/1.1	
175/70R13	C-140	3875	0,20	160	580	176	265	7.6/1.1	
165/70R13	I-391	3973	0,20	210	580	176(165)	265	7.6/1.1	
175/70R13	I-391	3973	0,20	210	580	176(165)	265	7.6/1.1	
175/70R13	RALLY-2000	3875	0,20	190	580	177	265	8.3/1.1	
195/65R15	URAL-2000	3875	0,20	190	580	177	265	7.6/1.1	
205/70R14	I-371	5686	0,21	190	652	206	295	11.7/1.4	

-1-                      -2-                      -3-                      -4-                      -5-                      -6-                      -7-                      -8-                      -9-                      -10-

Fork-Lift Machines Tyres

4,00-10	C-91	1960	0,20	-	492	110	230	4.9/0.6	
5,00-10	B-19AM	10980	0,23	30	780	264	353	22.7/3.0	
5,00L-12	F-232								
6,00-10	C-94								
6,00-13	C-95								
1060/75-1563	F-201	10980	0,23	30	780	264	353	22.7/3.0	

### Agricultural Tyres

Size	Model	Ply rate	Rim type	Max Load kgf	Max Speed km/h	Pressure kgf/cm <sup>2</sup>	Outer diam. mm+1%	Section Width mm	Static Radius mm+1%	Weight kg	Tread Pattern
-1-	-2-	-3-	-4-	-5-	-6-	-7-	-8-	-9-	-10-	-11-	-12-
8,3-20	B-105A	8	W178(W7)	850	30	2.5	950	211	448	37	
7,50-20	B-103	6		850	30	2.5	910	205	430	27	
11,2-20	F-35	8	W10, (W7,W9)	1175	30	2.1	985	284	460	45	